Dunloplan

MERO Elast

Description:

Type: Dissipative, resilient floorcovering according to EN 649, fine, directional marbled.
Surface PUR-coated.

Form supplied:

Thickness:	2.0 mm
Tiles:	608 x 608 mm
Sheets on request:	length 15 m, width 2 m (30 m²)
Pallet:	600 tiles loose = 221.80 m²

Colours:

		Tiles 2.0 mm Sheets 2.0 mm
Stock colour:	pastell grey	964 F/B
Special colour on request:	sahara beige	961 F/B
Special colour on request:	blue	966 F/B
Special colour on request:	silver grey	965 F/B
Special colour on request:	green	967 F/B

Technical data:

Weight EN 430:	approx. 3,500 g/m²
Residual indentation EN 433:	≤ 0.1 mm
Dimensional stability EN 434:	≤ 0.4 %
Light fastness ISO 105-B02:	≥ 6
Electrical properties EN 14041:	dissipative
Conductivity resistance EN 1081:	**< 10^8 Ohm**
Treading test EN 1815:	< 2 kV
Electrical insulation value VDE 0100:	> 5 x 10^4 Ohm
Sound absorption DIN 52210:	approx. 4 dB
Thermal resistivity DIN 52612:	approx. 0.01 m² K/W
Abrasive loss EN 660-1:	Group M
Fire resistance DIN EN 13501-1:	B_{fl}-s1
Exposure to water:	resistant
Exposure to chemicals EN 423:	resistant, depending on concentration and contact time of aggressive chemicals
Castor chair resistance EN 425:	suitable for castors type W

Cleaning and care: For cleaning and care please see the recommendation

Classification EN 685:

2.0 mm:



CE 06 EN 14041:06 1488-CPD-0043



We reserve all rights for technical improvements.